

Product Specifications

| | | |
|--|--|---|
| Style Number | VV675 | |
| Construction | Mineral Core | |
| Edge Profile | Enhanced Painted Bevel | |
| Nominal Dimensions | 9" wide, lengths of 33", 53" and 86" | |
| | US Units | Metric Units |
| | ----- | |
| Actual Product Width | 9.06" | 23 cm |
| Actual Product Length | Multiple Lengths 33.46", 53.14" and 86.61" | Multiple Lengths 85 cm, 135 cm and 220 cm |
| Overall Product Thickness | 0.354" | 9 mm |
| Core Thickness | 0.315" | 8 mm |
| Attached Underlayment | Attached Cork | |
| Attached Underlayment Thickness | 0.039" | 1 mm |
| Finish | Scratchless | |
| Profile | Angle/Tap | |
| Country of Origin | Imported | |

Packaging

| | | |
|-------------------------|-------------|-----------|
| Area per Box | 21.79 sq ft | 2.02 sq m |
| Pieces per Box | 18 pcs | |
| Weight per Box | 55.12 lbs | 25 kg |
| Boxes per Pallet | 48 boxes | |



3015 Suffolk Oak

Colors



Scratchless 9x86

Performance

| | |
|-------------------------------------|-----------------|
| Static Load (ASTM F970) | Passes |
| Resistance to Heat (ASTM F1514) | Passes |
| Resistance to Chemicals (ASTM F925) | Passes |
| Radiant Panel (ASTM E648) | Passes, Class I |
| Slip Resistance (ASTM D2047) | ADA compliant |

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Warranties


USF Lifetime

Residential Resilient Limited Warranty - Defects, Wear, Waterproof, Petproof

30 Year Scratch


20 Year Light Commercial

Coordinating Trim




Baby Threshold*

BT6NC | 94"




T-Molding*

TM6NC | 94"



Quarter Round

QTRNC | 94"



Flush Stairnose

FS8NC | 94"

*Packaged with molding track

Stair Tread



Stair Tread

03Z70 | 48"