



District

LVP COLLECTION



LI-DT04 Brentwood

Lions Floor District collection was created with exclusive patterns topped with intricate wood grain embossed finishes to coordinate with various design options. Featuring a fiberglass-reinforced structure, the product delivers dimensional stability that yields high traffic tolerance. The District collection is an embodiment of timeless aesthetics and performance-driven functionality.



Waterproof



Indent Resistant



Sound Tested



Pet Friendly



Formaldehyde Free



Phthalate Free

SPECIFICATIONS

| | | | | | | | |
|-----------------|------------|-------------------|---------------------|-----------|-------------|-----------------|------------|
| Material Type | LVP | Edge Profile | Square Edge | Per Box | 20 pieces | 48.33 sq.ft. | 39 lbs. |
| Plank Size | 4' x 7.25" | Installation Type | Glue Down | Pallet | 60 boxes | 2,899.54 sq.ft. | 2,390 lbs. |
| Total Thickness | 2 mm | Plank Repeat | 10 | Container | 1,140 boxes | 55,091 sq.ft. | |
| Wear Layer | 6 mil | Texture/Style | Wood Grain Embossed | | | | |
| Attached Pad | No | Finish | UV Aluminum Oxide | | | | |

Luxury Vinyl Plank

Fiberglass-Reinforced Structure



CERTIFIED BY
SCS Global Services

COLORS



LI-DT01 Billings



LI-DT02 Chesterbrook



LI-DT03 Los Alamos



LI-DT04 Brentwood



LI-DT05 Brighton



LI-DT06 Ardmore



LI-DT07 Carmel



LI-DT08 Clayton



LI-DT09 Bellevue



LI-DT10 Irvine



LI-DT11 Arlington



LI-DT12 Westfield

TESTING

| | | | | | |
|------------|-------------------------------|-----------------|------------------------------|--|------------|
| ASTM E648 | Fire Rating | Class 1 or 2 | ASTM F410 | Average Wear Layer Thickness | 6.0 mil |
| ASTM E303 | Surface Friction (in BPN) | Dry 77 Wet 37 | ASTM F2199 | Dimensional Stability, Curl After Heat | Passes |
| ASTM F2421 | Size and Squareness | Above average | ASTM F1514 | Resistance to Heat | Passes |
| E492 | IIC - Impact Sound Rating | 39 db | ASTM F1514 | Resistance to Light | Passes |
| E90 | STC - Sound Transmission Loss | 53 db | ISO 24337 | Variance of Thickness | Above avg. |
| ASTM D1308 | Stain Resistance | No Stain | Floor Score Certified | | |