

5 SERIES VENTILATION HOODS

Clear the Air





In a kitchen full of aromas, allow the scent of fresh food to emerge above the rest. Viking Professional Ventilation offers classic Viking appeal – heavy-duty, yet stylish, with new dimmable LED lighting and the ability to easily adjust the fan speed while cooking. Clear the air with Viking Professional Ventilation systems designed to complete your Viking kitchen.



12"H. Wall Hood*



18"H. Wall Hood*



18"H. Chimney Wall Hood



18"H. Chimney Island Hood

Built-In Custom Ventilator models available

*Wall hoods shown with optional duct cover



5 SERIES VENTILATION HOOD FEATURES

Heavy-Duty Professional Design

- Backlit LED knobs extend and illuminate to control lighting level and fan speed, then fully retract when not in use
- Seamless design provides a refined finish to your kitchen





Ouiet, Efficient, and Maintenance-Free Ventilators*

- 460 CFM interior-power ventilator comes standard and quietly delivers powerful smoke and odor removal - 12"H. only
- Tough-box ventilator housing protects blower and quietly removes smoke and odor - 18"H. only
- Quietest hood and ventilator combination in the industry -18"H. only
- Multi-speed ventilator control knob allows precise adjustment to desired fan speed
- Maintenance-free ventilators never need to be cleaned with the commercial-type hood filters doing the dirty work
- Cook with peace of mind as the built-in heat sensor activates the ventilator to full power if cooking temperatures reach uncomfortable levels
- * Ventilators must be purchased separately for 18"H. Hoods and are available in internal, external, and in-line models

Bright LED Lighting

- Dimmable lighting controls provide custom illumination for enhanced surface cooking visibility
- Long-life LED light bulbs are energy efficient and easily replaceable
- Heat lamps conveniently keep food warm until ready to serve (not available on Island Hoods) - 18"H. only

Easy Maintenance and Clean-up

- Commercial-type baffle filters efficiently remove heat and grease vapors from the air
- Stainless steel dishwasher-safe filters are easily removed for quick cleaning
- Low-profile filter system reduces interior hood space, leaving less surface to clean
- Removable trough collects liquefied grease for convenient disposal - 18"H. only

Accessory Installation Products

- Duct covers
- Backsplashes
- Make-up air damper kits
- Recirculating hood conversion kits 12"H. only
- Warming shelf panels (wall hoods) 18"H. only
- Internal ventilator kits 18"H. only
- Exterior power ventilator kits 18"H. only
- In-line ventilator kits 18"H. only
- Duct silencers 18"H. only

Exclusive Finishes

Available in Stainless Steel (SS), Black (BK),
White (WH), Apple Red (AR), Burgundy (BU),
Cobalt Blue (CB), Graphite Gray



- 3-year full complete product
- 90-day full cosmetic parts such as glass, painted items and decorative items
- 5-year limited ventilator motor







12"H. Interior 18"H. Interior

12"H. HOOD SPECIFICATIONS*

VWH 12"H. Wall Hoods with Standard Ventilator				
Description	VWH53012	VWH53612		
Overall width	29-7/8" (75.9 cm)	35-7/8" (91.1 cm)		
Overall depth	21" (53.3 cm)			
Overall height	12" (30.5 cm)			
Interior ventilator kit	460 CFM Standard			
Interior duct size**	7" (17.8 cm)			
Interior - Maximum amps	4.9			
Approximate shipping weight	56 lbs. (25.2 kg) 60 lbs. (27 kg)			

^{*} Always refer to installation instructions included with product or visit vikingrange.com/specs for the most accurate cutouts and installation requirements.

18"H. HOOD SPECIFICATIONS*

VWH 18"H. Wall Hoods						
Description	VWH53048	VWH53648	VWH54248	VWH54848	VWH56048	
Overall/duct cover width	29-7/8" (75.9 cm)	35-7/8" (91.1 cm)	41-7/8" (106.4 cm)	47-7/8" (121.6 cm)	59-7/8" (152.1 cm)	
Overall depth	24" (61.0 cm)					
Overall height	18" (45.7 cm)					
Duct cover depth	12" (30.5 cm)					
Duct cover height	12" (30.5 cm)					
Heat lamps	1	1	1	2	3	
Interior ventilator kits	VINV300/600/1200	VINV300/600/1200	VINV600/1200	VINV1200*	VINV1200*	
Exterior ventilator kits	DEV900/1200*	DEV900/1200*	DEV900/1200*	DEV1200*/1500**	DEV1200*/1500**	
In-line ventilator kits	DIL1200	DIL1200	DIL1200	DIL1200	DIL1200	
Interior duct size	7"/10" (17.8/25.4 cm)	7"/10" (17.8/25.4 cm)	7"/10" (17.8/25.4 cm)	10" (25.4 cm)	10" (25.4 cm)	
Exterior duct size	10" (24.5 cm)					
Interior—Maximum amps	4.2/5.2/8.2	4.2/5.2/8.2	5.2/8.2	10.8	10.8	
Exterior—Maximum amps	8.0/5.3	8.0/5.3	8.0/5.3	7.8/8.5	7.8/8.5	
In-Line—Maximum amps	5.3/7.2	5.3/7.2	5.3/7.2	9.6	10.0	

VCWH 18"H. Chimney Wall Hoods						
Description	VCWH53048	VCWH53648	VCWH54248	VCWH54848	VCWH56048	
Overall width	29-7/8" (75.9 cm)	35-7/8" (91.1 cm)	41-7/8" (106.4 cm)	47-7/8" (121.6 cm)	59-7/8" (152.1 cm)	
Overall depth			24" (61.0 cm)			
Overall height	18" (45.7 cm)					
Duct cover width	12" (30.5 cm)	12" (30.5 cm)	12" (30.5 cm)	18" (45.7 cm)	24" (61.0 cm)	
Duct cover depth	12" (30.5 cm)					
Duct cover height	12" (30.5 cm) to 24" (61.0 cm)					
Heat lamps	1	1	1	2	3	
Interior ventilator kits	VINV300/600	VINV300/600	VINV600	VINV1200**	VINV1200**	
Exterior ventilator kits	DEV900/1200**	DEV900/1200**	DEV900/1200**	DEV1200**/1500***	DEV1200**/1500***	
In-line ventilator kits	DIL1200	DIL1200	DIL1200	DIL1200	DIL1200	
Interior duct size	7" (17.8 cm)	7" (17.8 cm)	7" (17.8 cm)	10" (25.4 cm)	10" (25.4 cm)	
Exterior duct size	10" (24.5 cm)					
Interior—Maximum amps	4.2/5.2	4.2/5.2	5.2	10.8	10.8	
Exterior—Maximum amps	8.0/5.3	8.0/5.3	8.0/5.3	7.8/8.5	7.8/8.5	
In-Line—Maximum amps	5.3/7.2	5.3/7.2	5.3/7.2	9.6	10.0	

^{**} Disregard when using recirculating kits. 460 CFM blower is shipped with hood. Maximum duct run is 50 ft.

18"H. HOOD SPECIFICATIONS CONTINUED*

VCIH 18"H. Chimney Island Hoods					
Description	VCIH53608	VCIH54208	VCIH55408	VCIH56608	
Overall width	35-7/8" (91.1 cm)	41-7/8" (106.4 cm)	53-7/8" (136.8 cm)	65-7/8" (167.3 cm)	
Overall depth	30" (76.2 cm)				
Overall height	18" (45.7 cm)				
Duct cover width	12" (30.5 cm)	12" (30.5 cm)	18" (45.7 cm)	24" (61.0 cm)	
Duct cover depth	12" (30.5 cm)				
Duct cover height	12" (30.5 cm) or 24" (61.0 cm) or 36" (91.4 cm)				
Interior ventilator kits	VINV600	VINV600	VINV1200**	VINV1200**	
Exterior ventilator kits	DEV900/1200**	DEV900/1200**/1500***	DEV1200**/1500***	DEV1200**/1500***	
In-line ventilator kits	DIL1200	DIL1200	DIL1200	DIL1200	
Interior duct size	7" (17.8 cm)	7" (17.8 cm)	10" (25.4 cm)	10" (25.4 cm)	
Exterior duct size	10" (24.5 cm)				
Interior—Maximum amps	4.2/5.2	5.2/8.2	8.9	9.3	
Exterior—Maximum amps	7.4/4.7	7.4/4.7/5.5	5.6/6.4	6.4/7.4	
In-Line—Maximum amps	4.7/6.5	3.9/5.7	7.4	7.4	

VBCV 18"H. Wall Custom Ventilator System					
Description	VBCV53638	VBCV54238	VBCV54838	VBCV56038	
Overall width	33-7/16" (84.9 cm)	39-7/16" (100.2 cm)	45-7/16" (115.4 cm)	57-7/16" (145.9 cm)	
Overall depth	21-7/16" (54.5 cm)				
Heat lamps	1	1	2	3	
Interior ventilator kits	VINV300/600/1200**	VINV600/1200**	VINV1200**	VINV1200**	
Exterior ventilator kits	DEV900/1200**	DEV900/1200**	DEV1200**/1500***	DEV1200**/1500***	
In-Line ventilator kits	DIL1200	DIL900/1200	DIL1200	DIL1200	
Interior duct size	7"/10" (17.8/25.4 cm)	7"/10" (17.8/25.4 cm)	10" (25.4 cm)	10" (25.4 cm)	
Exterior duct size	10" (25.4 cm)				
Interior—Maximum amps	4.2/5.2	10.8	10.8	10.8	
Exterior—Maximum amps	8.0/5.3	8.0/5.3	7.8/8.5	7.8/8.5	
In-Line—Maximum amps	5.3/7.2	5.3/7.2	9.6	10.0	

^{**} A 1,200 CFM interior or exterior-power ventilator should be used when installed over range/rangetop with gas chargrill. Maximum duct run is 50 ft.

NOTE: Maximum amp rating for hoods includes recommended ventilator kit rating; All products must be hard wired 2-wire with ground. An interior or exterior-power ventilator kit must be purchased for installation with all 18"H. hoods.





^{***} It is recommended that the 1,500 CFM ventilator be used with longer duct runs. Maximum duct run is 75 ft.