

NightOwl SP > Product Categories > Cameras

Q

Search

FTD8 Series Camera



Troubleshooting

Component Model #	CM-FTD8LS-B (Purchase Additional Cameras TBD) (Support)
Resolution	3840 x 2160 (4k)



Hi. Need any help?



Series	FTD8
Video Transmission Technology	TVI
Field of View	80°
2-Way Audio	Yes
Microphone	Yes
Speaker	Yes (Preset Voice Messages / Siren)
Night Vision Range	(up to) 100 ft.
Spotlight	Yes (1 per Camera)
Power Supply	12V 2A (Purchase)
Min / Max Power In	Min 10V / Max 18V
Maximum Cable Length	160 ft. (Purchase)
Video Connection Type	BNC
Weather-Resistant Rating	IP-65
Operational Temperature Range	-4°F - 140°F
Regulation	FCC

Return to top ^

Recently viewed articles

FTD8 Series

Recorder and Camera Compatibility

Night Owl Protect CMS Download and Setup Guide

Upgrading your Bluetooth® Recorder's Firmware

FTD4 Series

Related articles

Basic Troubleshooting - Cameras

FTD8 Series

FTD8 Series Dome Camera Spec Sheet

Night Owl Protect CMS Download and Setup Guide

Night Owl Protect App, CMS and Recorder Videos

NightOwl SP