

Product Specifications

Style Number	VV024	
Construction	Waterproof Foamed Core	
Edge Profile	Micro Bevel	
Nominal Dimensions	7" wide, 48" long	
	US Units	Metric Units
Actual Product Width	7.13"	18 cm
Actual Product Length	48.03"	122 cm
Wear Layer Thickness	20 mil (0.02")	0.5 mm
Overall Product Thickness	0.314"	8 mm
Core Thickness	0.256"	6.5 mm
Attached Underlayment	Attached Cork	
Attached Underlayment Thickness	0.059"	1.5 mm
Finish	UV Acrylic	
Installation Methods	Floating or Direct Glue	
Profile	Angle/Tap	
Country of Origin	Imported	

Packaging

Area per Box	38.03 sq ft	3.53 sq m
Pieces per Box	16 pcs	
Weight per Box	63.05 lbs	28.59 kg
Boxes per Pallet	35 boxes	



210 Kingswood Oak

Colors



COREtec Originals Classics VV024



716 Midway Oak



3036 Mulford Oak



5060 Stockton Oak



5076 Brixton Oak



7034 Eastwell Oak

Color Variation: V2 - Slight



8013 Foxbury Oak

Performance

Static Load (ASTM F970)	Passes
Residual Indentation (ASTM F1914)	Passes
Resistance to Heat (ASTM F1514)	Passes
Resistance to Light (ASTM F1515)	Passes
Resistance to Chemicals (ASTM F925)	Passes
Radiant Panel (ASTM E648)	Passes, Class I
Slip Resistance (ASTM D2047)	ADA compliant

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Warranties

USF Lifetime

[Residential Resilient Limited Warranty - Defects, Wear, Waterproof, Petproof](#)

10 Year Light Commercial

Com Ub Bond 4100/4151

Certifications


FloorScore Certified

GreenGuard (Certification, Gold, Private Label) Certified




COREtec Originals Classics VV024

Coordinating Trim




Baby Threshold*

BT7CT | 94"
01V02 | 94"
01V06 | 94"




T-Molding*

TM7CT | 94"
02V24 | 94"
02V28 | 94"




Quarter Round

QTRCT | 94"
01V27 | 94"
01V31 | 94"




Overlap Stairnose*

01V76 | 94"
01V80 | 94"



Flush Stairnose

FS7HU | 94"
02V01 | 94"
02V06 | 94"



Overlap Reducer

01V52 | 94"
01V56 | 94"

*Packaged with molding track

Coordinating Metal Trim



Reducer

USC20
USC21
USC25



T-Mold

USC23
USC24



Stair Cap

USC17
USC18

Finish

Satin Silver
Satin Nickel
Dark Bronze

Installation Range

Profile Size	Installation Range
3.5mm	1.5mm to 3.5mm heights
5.5mm	3.6mm to 5.5mm heights
8mm	6mm to 8mm heights

Stair Tread



Stair Tread

03Z70 | 48"