

**Product Specifications**

<b>Style Number</b>	VV800
<b>Construction</b>	Solid Polymer Core
<b>Edge Profile</b>	Enhanced Integrated Bevel
<b>Nominal Dimensions</b>	7" wide, 48" long

	US Units	Metric Units
<b>Actual Product Width</b>	7.13"	18 cm
<b>Actual Product Length</b>	49"	124 cm
<b>Wear Layer Thickness</b>	20 mil (0.02")	0.5 mm
<b>Overall Product Thickness</b>	0.236"	6 mm
<b>Core Thickness</b>	0.197"	5 mm
<b>Attached Underlayment</b>	Attached Cork	
<b>Attached Underlayment Thickness</b>	0.039"	1 mm
<b>Installation Methods</b>	Floating or Direct Glue	
<b>Profile</b>	Angle/Tap	
<b>Country of Origin</b>	Imported	

**Packaging**

<b>Area per Box</b>	16.97 sq ft	1.57 sq m
<b>Pieces per Box</b>	7 pcs	
<b>Weight per Box</b>	36.2 lbs	16.42 kg
<b>Boxes per Pallet</b>	70 boxes	



2035 Essex Maple

**Colors**



# COREtec Pro Premium VV800

## Performance

Static Load (ASTM F970)	Passes
Residual Indentation (ASTM F1914)	Passes
Resistance to Heat (ASTM F1514)	Passes
Resistance to Light (ASTM F1515)	Passes
Resistance to Chemicals (ASTM F925)	Passes
Radiant Panel (ASTM E648)	Passes, Class I
Slip Resistance (ASTM D2047)	ADA compliant

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

## Warranties


Residential Resilient Limited Warranty - Defects, Wear, Waterproof, Petproof

15 Year Light Commercial


## Coordinating Trim




**Baby Threshold\***  
BT7CT | 94"



**T-Molding\***  
TM7CT | 94"



**Quarter Round**  
QTRCT | 94"



**Flush Stairnose**  
FS5CT | 94"

\*Packaged with molding track

## Coordinating Metal Trim



**T-Mold**  
USC17



**Stair Cap**

**Finish**  
Satin Silver

USC24

**Satin Nickel**

## Installation Range

Profile Size	Installation Range
3.5mm	1.5mm to 3.5mm heights
5.5mm	3.6mm to 5.5mm heights
8mm	6mm to 8mm heights

## Stair Tread



**Stair Tread**  
03Z70 | 48"