



HD ²³ **PUREGRAIN**
HIGH-DEF

Style Name: Nurture

Style Number: D2021

Thickness: 5 mm

AC Rating: AC4 / Equivalent to 20 mil

Core Thickness: 4 mm

Core Composition: High Density Rigid Core

Attached Underlayment: 1.0 mm IXPE

Embossing: Digital Emboss

Surface Finish: Evertuff® with Aluminum Oxide

Nominal Dimensions: 7" x 48"

Actual Dimensions: 6.65" x 48" (169.91mm W x 1220mm L)

Unique Pattern Repeat: 35 Unique Planks

Edge: Natural Painted

Gloss Level: Matte

Traffic: Residential, Light Commercial

Locking Mechanism: One2Click® Angle/Angle

*All specifications are subject to normal manufacturing tolerances.

6001 Shoreline

6002 Seamist

6003 Mosaic

6004 Keystone

6005 Pandora

6006 Willow

6007 Drifter

6008 Canyon

6009 Renew

6010 Cavern

6011 Hazel

6012 Timber

Packaging

Pieces per carton: 10

Square feet per carton: 22.16

22 pallets per truckload

Boxes per pallet: 50

Square feet per pallet: 1,108

24,376 sq. ft. per truckload

Pallet dimensions: 50" x 40" x 26.65"

Weight per pallet: 1,770 lbs

Technical

IIC Sound Rating (ASTM E492): 61

Residual Indentation (ASTM F1419): Passes

Dimensional Stability (ASTM F2199): Passes

Resistance to heat (ASTM F1514): Passes

Critical Radiant Flux (ASTM E648): Class 1

Slip Resistance (ASTM C1028): ADA compliant

STC Sound Rating (ASTM E90): 53

Static Load (ASTM F970): Pending

Chemical Resistance (ASTM F925): Passes

Resistance to light (ASTM F1515): Passes

Optical Smoke Density (ASTM E662): Pending

WARRANTY

Lifetime Residential • 10 Year Commercial • Lifetime Waterproof and Pet

*Exclusions: Non owner occupied residential installations, outdoor installations, residential areas that are prone to being wet (bathrooms, laundry areas, kitchens, etc.), stairs, and areas that receive excessive equipment wear such as home gyms. Other exclusions may apply. Recommended carpet care and routine maintenance must be conducted to maintain warranty coverage.



www.engineeredfloors.com

866.706.9745

info@engineeredfloors.com