

NIKOLATESLA Series

Induction Technology with Integrated Aspiration



INTRODUCING: NIKOLATESLA Series


NIKOLATESLA PLUS FEATURES



BRIDGE 70NES



The special Bridge Zones can work both individually or combined for a more homogenous cooking using both baking pans and large pots. Thanks to this technology it is the cooktop's surface that adapts itself to the type of pots being used.



AIRMATIC



The auto aspiration adjusts automatically to the number and power of the used cooking zones.



CFRAMIC FILTERS



This recirculating filter is suitable for the most challenging cooking environment, given its superior ability to filter and purify the air. The new Elica Technology is able to achieve filtering threshold of 82% against the market average of 60%. it can be regenerated up to 5 years if placed in oven at 390° F for 45 minutes every 2/3 months.



POT DETECTOR



Automatically detects a pot on a cooking zone and sends a signal to the hood. Elica hoods with STREAM technology will turn on automatically.



TEMPERATURE MANAGER



Cooked dishes will always be perfect when you use this function that lets you set the cooktop with three programs (100°, 160°, and 200° F) the temperature has been optimized for both very delicate cooking (mousse, sauces, keeping dishes warm) as well as cooking at high power (boiling)




STOP&GO



If you are interrupted while cooking, or you have to go into another room, or you just want a break, with just a single movement, pressing the Stop&Go button, you can switch off all the cooking zones and walk away with complete confidence and safety.

NIKOLATESLA Series

FOR THOSE WHO LIKE THINKING OUTSIDE THE BOX:



NIKOLATESLA SWITCH







REVOLUTIONARY COOKING

INDUCTION TECHNOLOGY WITH BUILT-IN ASPIRATION THAT COMBINES ITALIAN DESIGN WITH FUNCTIONALITY

NikolaTesla Switch is the latest Induction Cooktop with built-in Aspiration by Elica, with innovative functions and unique performance, representing the highest expression of technology and design.

Available in a sophisticated black ceramic glass finish and measures 36" in width. The central disk which allows 360°- degree rotation has two exterior finishes - on one side is black glass and on the other is steel. When closed on either side (black glass or steel), the central disk is completely flush with the cooktop surface, cleverly concealing the aspiration system. High CFM performance, approximately 5 times faster than the speed of rising fumes, ensures efficient fume and moisture extraction. Duct-out and recirculating versions.

NIKOLATESLA SWITCH

The completely smooth surface of the NikolaTesla simplifies cleaning. In addition, the dishwasher safe exclusively designed grease filter can be accessed from the top of the surface. Any spilled liquids during cooking will be captured in the cavity below the grease filter and can be easily removed by opening the drain valve and wiping out any residual with a cloth.

In the recirculating version, the high performing new generation ceramic carbon filters are accessible from the top of the cooktop. making cleaning and maintenance a cinch.

Fits seamlessly into any design concept for your kitchen. Elica's aspiration cooktops have been designed to guarantee maximum installation flexibility, leaving enough space for undercabinet storage thank to movable ducting.

Note: As a security measure, it is not recommended to install any other type of electric appliance, like dishwashers or ovens, in the free space underneath NikolaTesla.

EXCLUSIVE PLUS FEATURES















MANAGER DETECTOR




Completely invisible Aspiration System, turn it on and off with a Switch.



Touch Controls, fully control each cooking zone with the tip of a single finger.

LINE DRAWING



ASPIRATION SYSTEM

Controls	Duct-Out Direct Slider 8 Speeds + 2 Boost levels	8 Speeds +
Blower Type	400 CFM	400 CFM
Suction speed	5.1 m/s	5.1 m/s
Noise (sones)	2.2 - 5	2.2 - 5
Ventilation	160 W	160 W
Exit	6"	6"

INDUCTION COOKTOP

Power Consumption	7.4 kW
Electrical Frequency	50 - 60 Hz
Voltage	220 - 240 V
Cooking Zones	4
Each Burner Dimensions	7,1 x 7,9 inches
Each Burner Power	2,1 - 3,7kW
Boost Power	3,7kW
Bridge Zones	2

FUNCTIONS

EGG TIMER/ SPECIAL TIMER CHILD LOCK TEMPERATURE MANAGER STOP & GO AUTOMATIC HEAT UP WARMING FUNCTION POT DETECTOR SAFETY SHUT DOWN POWER LIMITATION RESIDUAL HEAT INDICATOR **BRIDGE ZONES**

Bridge Zones Power: Each induction module can supply max 3.7kW, so the 2 cooking zones connected to the same induction module can't be setted up at booster level together (3.7 + 3.7 per module)

MODEL



MODEL

NIKOLATESLA SWITCH 36" ENTS436BLO Black Tempered Glass

PARTS INCLUDED

Qty 1 - 6 layer anodized aluminum mesh grease filter (pre-installed)

Qty 1 - Ducted Out cartridge (pre-installed)

Qty 1 - Recirculation cartridge

Qty 4 - Ceramic carbon filters and removal ribbon

Qty 1 - Reducer Joint

Qtv 1 - 3 " x 10" short metal duct transition

Qty 1 - 3 " x 10" long metal duct transition

Qty 1 - Joint Tape

Qty 1 - Hardware Pack (contains mounting clips, seam tape, installation instructions)

NIKOLATESLA ONE







FUNCTIONALITY AND INNOVATION

ELICA'S FIRST INDUCTION COOKTOP WITH TECHNOLOGY INTEGRATED, COMBINING TWO KITCHEN APPLIANCES INTO ONE

With the advantages of cooking speed and easy maintenance common with induction cooktops, NIKOLATESLA ONE adds central ventilation for high performance capture of grease, smoke and odor.

Completely invisible Aspiration system, that can be easily controlled with the touch of your finger.

NIKOLATESLA ONE

The aspirating system, positioned in the central zone, reaches high performance levels, in terms of fume extraction, noise level and energy efficiency. Thanks to the direct communication with the cooktop, it is able to receive information from the cooking zones, and automatically calibrates the ideal aspiration level, so that the user only needs to worry about cooking, while at the same time reducing energy consumption.

With filters included the NikolaTesla One can be installed as ducted or recirculated.

EXCLUSIVE PLUS FEATURES














MANAGER DETECTOR








Drain valve can be opened to remove any residue or spilled liquid.

LINE DRAWING

MODEL



FUNCTIONS

EGG TIMER/ SPECIAL TIMER CHILD LOCK TEMPERATURE MANAGER STOP & GO BRIDGE ZONES AUTOMATIC HEAT UP WARMING FUNCTION COOKING ZONE TIMER POT DETECTOR SAFETY SHUT DOWN POWER LIMITATION




MODEL

NIKOLATESLA HP 33" ENT432BL Black Glass TRIM KIT 36"

KIT0155746 Stainless Steel

TRIM KIT DIMENSIONS



INDUCTION COOKTOP

Electrical Frequency 50 - 60 Hz 220 - 240 V Voltage Cooking Zones Each Burner Dimensions 180x200 mm Each Burner Power (2.1 - 3.7 kW) Boost Power 3.7 kW Bridge Zones

Power Consumption 7.4 kW

ASPIRATION SYSTEM

	Duct-Out	Recirculating
Controls	Direct Slider 9V+1I	Direct Slider 9V+1
Blower Type	400 CFM	400 CFM
Suction speed	5.1 m/s	5.1 m/s
Noise (sones)	2.2 - 5	2.2 - 5
Ventilation	160 W	160 W

PARTS INCLUDED

Qtv 1 - 6 layer anodized aluminum mesh grease filter (pre-installed)

Qty 1 - Ducted Out cartridge (pre-installed)

Qty 1 - Recirculation cartridge

Qty 4 - Ceramic carbon filters and removal ribbon

Qty 1 - Reducer Joint

Qty 1 - 3 " x 10" short metal duct transition

Qty 1 - 3 " x 10" long metal duct transition


Qtv 1 - Joint Tape

Qty 1 - Hardware Pack (contains mounting clips, seam tape, installation instructions)

INSTALLATION TYPE

NIKOLATESLA has been designed to adapt to different types of kitchens (All ducting should by supplied by installer).

TRADITIONAL INSTALLATION




ONE	
Α	32 11/16"
В	20 4/16"
С	31 31/16"
D	19 6/16"
Е	8 4/16"
F	7/16"
G	Min 1 15/16"

SWITCH	
А	36 1/16"
В	20 4/16"
С	31 31/16"
D	19 6/16"
Е	8 4/16"
F	7/16"
G	Min 1 15/16"

In its Duct-Out version, having installed the ducts outside the cabinets is optional, user can choose the ideal configuration according to its needs.

FLUSH MOUNTED




ONE	
Α	32 15/16"
В	20 8/16"
С	31 31/16"
D	19 6/16"
Е	8 4/16"
F	9/32"
G	7/16"

SWITCH	
А	36 1/16"
В	20 8/16"
С	31 31/16"
D	19 6/16"
Е	8 4/16"
F	9/32"
G	1/2"

DUCT-OUT

RECIRCULATING













For the Duct-Out version installation, it will be necessary to leave a high stand of 3.93" to allow space to the ducts on the ground.

Please note, most ducting insulation provided by the installer are rigid, images may vary from final installations results according to each user needs.

REALIZED BY ELICAMEX MARKETING TEAM

Typographic printing does not always reproduce original colors and materials faithfully.

Elica reserves the right to make changes to the data and details of the products in this catalogue, even without notice.

JUNE 2020



YEAR FULL WARRANTY

EARN A 3RD YEAR OF FULL **FACTORY** WARRANTY

COVERING ALL PARTS PLUS IN-HOME LABOR.

FOR U.S & CANADA USERS ONLY

By registering the NIKOLATESLA cooktop on the elica.com site, warranty is extended free of charge for 3 years. No additional costs for parts or in-home labor. Only at certain Elica authorized service centers. For valid warranty extension, register within 3 months form purchase.

https://elica.com/US-en/register-product



DISCOVER MORE elica.com







