





# **SPECIFICATIONS**

Active Display Area (mm)  Curvature  Flat  Panel Type  Rapid IPS  Panel Resolution  2560 x 1440 (WQHD)  Pixel Pitch (H x V)  Aspect Ratio  Brightness (nits)  Contrast Ratio  DCR  100000000:1  Signal Frequency  64.56~266.4KHz(H) / 48~180Hz(V)  ACTIVATED RANGE  Response time  1ms (GtG)  DYNAMIC REFRESH RATE TECHNOLOGY  HDR Support  Video ports  1 x DisplayPort (1.4) 2 x HDMI™ (2.0b)  USB ports  Audio ports  1x Headphone out  Viewing Angle  Anti-glare  Display Colors  1.07B (8 bits + FRC)  Power Type  External Adaptor  Power Input  Adjustment (Tilt)  -5° ~ 20°  Adjustment (Swivel)  Adjustment (Height)  Kensington Lock  Piss Piss (H) / 130 mm  Kensington Lock  View 12 x 24 x 4 x 250 mm (without Stand)  Carton Dimension (W X D X H)  Frameless Design  Pyes  PIP / PBP Function  N/A	Panel Size	27" (69 cm)
Panel Type         Rapid IPS           Panel Resolution         2560 x 1440 (WQHD)           Pixel Pitch (H x V)         0.2331(H)x0.2331(V)           Aspect Ratio         16:9           Brightness (nits)         300 (Typ.)           Contrast Ratio         1200:1           DCR         100000000:1           Signal Frequency         64.56~266.4KHz(H) / 48~180Hz(V)           ACTIVATED RANGE         48~180Hz           Refresh Rate         180Hz           Response time         1ms (GtG)           DYNAMIC REFRESH RATE         AMD FreeSync™           TECHNOLOGY         HDR Ready           Video ports         1 x DisplayPort (1.4)           2 x HDMI™ (2.0b)         USB ports           N/A         N/A           Audio ports         1x Headphone out           Viewing Angle         178° (H) / 178° (V)           Adobe RGB / DCI-P3 / sRGB         90% / 94% / 125%           Surface Treatment         Anti-glare           Display Colors         1.07B (8 bits + FRC)           Power Type         External Adaptor           Power Input         100~240V, 50/60Hz           Adjustment (Tilt)         -5° ~ 20°           Adjustment (Pivot)         -90° ~ 90° <tr< th=""><th>Active Display Area (mm)</th><th>596.736(H) x 335.664(V)</th></tr<>	Active Display Area (mm)	596.736(H) x 335.664(V)
Panel Resolution         2560 x 1440 (WQHD)           Pixel Pitch (H x V)         0.2331(H)x0.2331(V)           Aspect Ratio         16:9           Brightness (nits)         300 (Typ.)           Contrast Ratio         1200:1           DCR         100000000:1           Signal Frequency         64.56~266.4KHz(H) / 48~180Hz(V)           ACTIVATED RANGE         48~180Hz           Refresh Rate         180Hz           Response time         1ms (GtG)           DYNAMIC REFRESH RATE TECHNOLOGY         AMD FreeSync™           HDR Ready         1 x DisplayPort (1.4)           Video ports         1 x DisplayPort (2.0b)           USB ports         N/A           Audio ports         1x Headphone out           Viewing Angle         178° (H) / 178° (V)           Adobe RGB / DCI-P3 / sRGB         90% / 94% / 125%           Surface Treatment         Anti-glare           Display Colors         1.07B (8 bits + FRC)           Power Type         External Adaptor           Power Input         100~240V, 50/60Hz           Adjustment (Tilt)         -5° ~ 20°           Adjustment (Swivel)         -30° ~ 30°           Adjustment (Height)         0 ~ 130 mm           Kensington Lock	Curvature	Flat
Pixel Pitch (H x V)         0.2331(H)x0.2331(V)           Aspect Ratio         16:9           Brightness (nits)         300 (Typ.)           Contrast Ratio         1200:1           DCR         100000000:1           Signal Frequency         64.56~266.4KHz(H) / 48~180Hz(V)           ACTIVATED RANGE         48~180Hz           Refresh Rate         180Hz           Response time         Ims (GtG)           DYNAMIC REFRESH RATE TECHNOLOGY         AMD FreeSync™           HDR Ready         1 x DisplayPort (1.4)           Video ports         1 x DisplayPort (2.0b)           USB ports         N/A           Audio ports         1x Headphone out           Viewing Angle         178° (H) / 178° (V)           Adobe RGB / DCI-P3 / sRGB         90% / 94% / 125%           Surface Treatment         Anti-glare           Display Colors         1.07B (8 bits + FRC)           Power Type         External Adaptor           Power Input         100~240V, 50/60Hz           Adjustment (Tilt)         -5° ~ 20°           Adjustment (Swivel)         -30° ~ 30°           Adjustment (Height)         0 ~ 130 mm           Kensington Lock         Yes           Dimension (W x D x H)         613	Panel Type	Rapid IPS
Aspect Ratio       16:9         Brightness (nits)       300 (Typ.)         Contrast Ratio       1200:1         DCR       100000000:1         Signal Frequency       64.56~266.4KHz(H) / 48~180Hz(V)         ACTIVATED RANGE       48~180Hz         Refresh Rate       180Hz         Response time       1ms (GtG)         DYNAMIC REFRESH RATE TECHNOLOGY       AMD FreeSync™         HDR Ready       1 x DisplayPort (1.4)         Video ports       1 x DisplayPort (1.4)         2 x HDMI™ (2.0b)       2x HDMI™ (2.0b)         USB ports       N/A         Audio ports       1x Headphone out         Viewing Angle       178° (H) / 178° (V)         Adobe RGB / DCI-P3 / sRGB       90% / 94% / 125%         Surface Treatment       Anti-glare         Display Colors       1.07B (8 bits + FRC)         Power Type       External Adaptor         Power Input       100~240V, 50/60Hz         Adjustment (Tilt)       -5° ~ 20°         Adjustment (Pivot)       -90° ~ 90°         Adjustment (Height)       0 ~ 130 mm         Kensington Lock       Yes         Dimension (W x D x H)       613 x 228 x 539 mm (without Stand)         Carton Dimension (W X D X H)	Panel Resolution	2560 x 1440 (WQHD)
Brightness (nits)         300 (Typ.)           Contrast Ratio         1200:1           DCR         1000000000:1           Signal Frequency         64.56~266.4KHz(H) / 48~180Hz(V)           ACTIVATED RANGE         48~180Hz           Refresh Rate         180Hz           Response time         1ms (GtG)           DYNAMIC REFRESH RATE         TECHNOLOGY           HDR Ready         4MD FreeSync™           Video ports         1 x DisplayPort (1.4)           2 x HDMI™ (2.0b)         1x Headphone out           Viewing Angle         178° (H) / 178° (V)           Adobe RGB / DCI-P3 / sRGB         90% / 94% / 125%           Surface Treatment         Anti-glare           Display Colors         1.07B (8 bits + FRC)           Power Type         External Adaptor           Power Input         100~240V, 50/60Hz           Adjustment (Tilt)         -5° ~ 20°           Adjustment (Swivel)         -30° ~ 30°           Adjustment (Height)         0 ~ 130 mm           Kensington Lock         Yes           Dimension (W x D x H)         613 x 228 x 539 mm (without Stand)           Carton Dimension (W X D X H)         WW: 840 x 150 x 475 mm Outer:858 x 165 x 500 mm           Frameless Design         Yes <th>Pixel Pitch (H x V)</th> <th>0.2331(H)x0.2331(V)</th>	Pixel Pitch (H x V)	0.2331(H)x0.2331(V)
Contrast Ratio         1200:1           DCR         100000000:1           Signal Frequency         64.56~266.4KHz(H) / 48~180Hz(V)           ACTIVATED RANGE         48~180Hz           Refresh Rate         180Hz           Response time         1ms (GtG)           DYNAMIC REFRESH RATE TECHNOLOGY         AMD FreeSync™           HDR Ready         1x DisplayPort (1.4)           Video ports         1x DisplayPort (1.4)           2 x HDMI™ (2.0b)         0.0           USB ports         N/A           Audio ports         1x Headphone out           Viewing Angle         178° (H) / 178° (V)           Adobe RGB / DCI-P3 / sRGB         90% / 94% / 125%           Surface Treatment         Anti-glare           Display Colors         1.07B (8 bits + FRC)           Power Type         External Adaptor           Power Input         100~240V, 50/60Hz           Adjustment (Tilt)         -5° ~ 20°           Adjustment (Swivel)         -30° ~ 30°           Adjustment (Height)         0 ~ 130 mm           Kensington Lock         Yes           Dimension (W x D x H)         613 x 228 x 539 mm (without Stand)           Carton Dimension (W X D X H)         WW: 840 x 150 x 475 mm Outer:858 x 165 x 500 mm <th>Aspect Ratio</th> <th>16:9</th>	Aspect Ratio	16:9
DCR         100000000:1           Signal Frequency         64.56~266.4KHz(H) / 48~180Hz(V)           ACTIVATED RANGE         48~180Hz           Refresh Rate         180Hz           Response time         1ms (GtG)           DYNAMIC REFRESH RATE TECHNOLOGY         AMD FreeSync™           HDR Support         HDR Ready           Video ports         1 x DisplayPort (1.4) 2 x HDMI™ (2.0b)           USB ports         N/A           Audio ports         1x Headphone out           Viewing Angle         178° (H) / 178° (V)           Adobe RGB / DCI-P3 / sRGB         90% / 94% / 125%           Surface Treatment         Anti-glare           Display Colors         1.07B (8 bits + FRC)           Power Type         External Adaptor           Power Input         100~240V, 50/60Hz           Adjustment (Tilt)         -5° ~ 20°           Adjustment (Swivel)         -30° ~ 30°           Adjustment (Height)         0 ~ 130 mm           Kensington Lock         Yes           Dimension (W x D x H)         613 x 228 x 539 mm 613 x 61 x 369 mm (without Stand)           Carton Dimension (W X D X H)         WW: 840 x 150 x 475 mm Outer:858 x 165 x 500 mm           Frameless Design         Yes	Brightness (nits)	300 (Typ.)
Signal Frequency  ACTIVATED RANGE  Refresh Rate  Response time  DYNAMIC REFRESH RATE TECHNOLOGY  HDR Support  Video ports  USB ports  Addio ports  Viewing Angle  Display Colors  Display Colors  Power Type Power Input  Adjustment (Tilt)  Adjustment (Swivel)  Adjustment (Height)  Kensington Lock  Dimension (W x D x H)  Frameless Design  I 804.56~266.4KHz(H) / 48~180Hz(V)  44~180Hz (266.4KHz(H) / 48~180Hz(V)  44~180Hz (266.4KHz(H) / 48~180Hz(V)  44~180Hz (180Hz) / 48~180Hz(V)  48~180Hz  41x DisplayPort (1.4)  2x HDMITM (2.0b)  41x Display (1.4)  40	Contrast Ratio	1200:1
ACTIVATED RANGE  Refresh Rate  Response time  DYNAMIC REFRESH RATE TECHNOLOGY  HDR Support  HDR Ready  Video ports  1 x DisplayPort (1.4) 2 x HDMI™ (2.0b)  USB ports  N/A  Audio ports  1 x Headphone out  Viewing Angle  178° (H) / 178° (V)  Adobe RGB / DCI-P3 / sRGB  90% / 94% / 125%  Surface Treatment  Display Colors  1.07B (8 bits + FRC)  Power Type  External Adaptor  Power Input  100~240V, 50/60Hz  Adjustment (Tilt)  -5° ~ 20°  Adjustment (Swivel)  Adjustment (Swivel)  Adjustment (Pivot)  Adjustment (Height)  Kensington Lock  Dimension (W x D x H)  Frameless Design  Yes  AMD FreeSync™  AMD FreeSync™  AMD FreeSync™  AMD FreeSync™  AMD FreeSync™  1.04  1.07	DCR	100000000:1
Refresh Rate  Response time  DYNAMIC REFRESH RATE TECHNOLOGY  HDR Support  HDR Ready  Video ports  1 x DisplayPort (1.4) 2 x HDMI™ (2.0b)  USB ports  N/A  Audio ports  1x Headphone out  Viewing Angle  178° (H) / 178° (V)  Adobe RGB / DCI-P3 / sRGB  Surface Treatment  Display Colors  1.07B (8 bits + FRC)  Power Type  External Adaptor  Power Input  100~240V, 50/60Hz  Adjustment (Tilt)  -5° ~ 20°  Adjustment (Swivel)  -30° ~ 30°  Adjustment (Pivot)  Adjustment (Height)  Kensington Lock  Pimension (W x D x H)  Carton Dimension (W X D X H)  Frameless Design  MDR Ready  AMD FreeSync™  Inmakesync™  AND FreeSync™  Inmakesync (1.4)  2 x HDMI™ (2.0b)  AND FreeSync™  Inmakesync (1.4)  2 x HDMI (2.0b)  And Justment (1.4)  And Justment (	Signal Frequency	64.56~266.4KHz(H) / 48~180Hz(V)
Response time1ms (GtG)DYNAMIC REFRESH RATE TECHNOLOGYAMD FreeSync™HDR Ready1 x DisplayPort (1.4) 2 x HDMI™ (2.0b)Video ports1 x Headphone outUSB portsN/AAudio ports1x Headphone outViewing Angle178° (H) / 178° (V)Adobe RGB / DCI-P3 / sRGB90% / 94% / 125%Surface TreatmentAnti-glareDisplay Colors1.07B (8 bits + FRC)Power TypeExternal AdaptorPower Input100~240V, 50/60HzAdjustment (Tilt)-5° ~ 20°Adjustment (Swivel)-30° ~ 30°Adjustment (Pivot)-90° ~ 90°Adjustment (Height)0 ~ 130 mmKensington LockYesDimension (W x D x H)613 x 228 x 539 mm 613 x 61 x 369 mm (without Stand)Carton Dimension (W X D X H)WW: 840 x 150 x 475 mm Outer:858 x 165 x 500 mmFrameless DesignYes	ACTIVATED RANGE	48~180Hz
DYNAMIC REFRESH RATE TECHNOLOGY  HDR Support  HDR Ready  1 x DisplayPort (1.4) 2 x HDMI™ (2.0b)  USB ports  N/A  Audio ports  1x Headphone out  Viewing Angle  178° (H) / 178° (V)  Adobe RGB / DCI-P3 / sRGB  90% / 94% / 125%  Surface Treatment  Display Colors  1.07B (8 bits + FRC)  Power Type  External Adaptor  Power Input  100~240V, 50/60Hz  Adjustment (Tilt)  -5° ~ 20°  Adjustment (Swivel)  Adjustment (Pivot)  Adjustment (Height)  Kensington Lock  Dimension (W x D x H)  Carton Dimension (W X D X H)  Frameless Design  HDR Ready  1 x Display Cit.4  1 x DisplayPort (1.4) 2 x HDMI™ (2.0b)  1 x DisplayPort (1.4) 2 x HDMI™ (2.0b) 1 x DisplayPort (1.4) 2 x HDMI 2 x HDMI 2 x HON 3 x DisplayPort (1.4) 2 x HDMI 3 x DisplayPort (1.4) 2 x HDMI 3 x DisplayPort	Refresh Rate	180Hz
HDR Support  HDR Ready  Video ports  1 x DisplayPort (1.4) 2 x HDMI™ (2.0b)  USB ports  N/A  Audio ports  1x Headphone out  Viewing Angle  178° (H) / 178° (V)  Adobe RGB / DCI-P3 / sRGB  90% / 94% / 125%  Surface Treatment  Display Colors  1.07B (8 bits + FRC)  Power Type  External Adaptor  Power Input  100~240V, 50/60Hz  Adjustment (Tilt)  -5° ~ 20°  Adjustment (Swivel)  Adjustment (Fivot)  Adjustment (Height)  Carton Dimension (W x D x H)  Frameless Design  Al x DisplayPort (1.4)  2 x HDMI™ (2.0b)  1.4 x DisplayPort (1.4)  2 x HDMI  1.4 x DisplayPort (1.4)  2 x HDMI 1.4 x DisplayPort (1.4)  2 x DisplayPort (1.4	Response time	1ms (GtG)
Video ports  1 x DisplayPort (1.4) 2 x HDMI™ (2.0b)  N/A  Audio ports  1x Headphone out  Viewing Angle  178° (H) / 178° (V)  Adobe RGB / DCI-P3 / sRGB  90% / 94% / 125%  Surface Treatment  Display Colors  1.07B (8 bits + FRC)  Power Type  External Adaptor  Power Input  100~240V, 50/60Hz  Adjustment (Tilt)  -5° ~ 20°  Adjustment (Swivel)  Adjustment (Pivot)  Adjustment (Height)  Carton Dimension (W x D x H)  T x DisplayPort (1.4) 2 x HDMI™ (2.0b)  N/A  I x DisplayPort (1.4) 2 x HDMI™ (2.0b)  N/A  I x DisplayPort (1.4) 2 x HDMI™ (2.0b)  N/A  I x DisplayPort (1.4) 2 x HDMI™ (2.0b)  N/A  I x Headphone out  I x Headphone out  I ves  Surface Treatment  Anti-glare  1.07B (8 bits + FRC)  External Adaptor  100~240V, 50/60Hz  Adjustment (Tilt)  -5° ~ 20°  Adjustment (Fivot)  -90° ~ 90°  Adjustment (Pivot)  4 Signal (1.4) 2 x HDMI™ (2.0b)  N/A  Anti-glare  1.07B (8 bits + FRC)  External Adaptor  1.07B (8 bits + FRC)  2.0°		AMD FreeSync™
2 x HDMI	HDR Support	HDR Ready
Audio ports         1x Headphone out           Viewing Angle         178° (H) / 178° (V)           Adobe RGB / DCI-P3 / sRGB         90% / 94% / 125%           Surface Treatment         Anti-glare           Display Colors         1.07B (8 bits + FRC)           Power Type         External Adaptor           Power Input         100~240V, 50/60Hz           Adjustment (Tilt)         -5° ~ 20°           Adjustment (Swivel)         -30° ~ 30°           Adjustment (Pivot)         -90° ~ 90°           Adjustment (Height)         0 ~ 130 mm           Kensington Lock         Yes           Dimension (W x D x H)         613 x 228 x 539 mm (without Stand)           Carton Dimension (W X D X H)         WW: 840 x 150 x 475 mm Outer:858 x 165 x 500 mm           Frameless Design         Yes	Video ports	
Viewing Angle         178° (H) / 178° (V)           Adobe RGB / DCI-P3 / sRGB         90% / 94% / 125%           Surface Treatment         Anti-glare           Display Colors         1.07B (8 bits + FRC)           Power Type         External Adaptor           Power Input         100~240V, 50/60Hz           Adjustment (Tilt)         -5° ~ 20°           Adjustment (Swivel)         -30° ~ 30°           Adjustment (Pivot)         -90° ~ 90°           Adjustment (Height)         0 ~ 130 mm           Kensington Lock         Yes           Dimension (W x D x H)         613 x 228 x 539 mm (without Stand)           Carton Dimension (W X D X H)         WW: 840 x 150 x 475 mm Outer:858 x 165 x 500 mm           Frameless Design         Yes	USB ports	N/A
Adobe RGB / DCI-P3 / sRGB       90% / 94% / 125%         Surface Treatment       Anti-glare         Display Colors       1.07B (8 bits + FRC)         Power Type       External Adaptor         Power Input       100~240V, 50/60Hz         Adjustment (Tilt)       -5° ~ 20°         Adjustment (Swivel)       -30° ~ 30°         Adjustment (Pivot)       -90° ~ 90°         Adjustment (Height)       0 ~ 130 mm         Kensington Lock       Yes         Dimension (W x D x H)       613 x 228 x 539 mm (without Stand)         Carton Dimension (W X D X H)       WW: 840 x 150 x 475 mm Outer:858 x 165 x 500 mm         Frameless Design       Yes	Audio ports	1x Headphone out
Surface TreatmentAnti-glareDisplay Colors1.07B (8 bits + FRC)Power TypeExternal AdaptorPower Input100~240V, 50/60HzAdjustment (Tilt)-5° ~ 20°Adjustment (Swivel)-30° ~ 30°Adjustment (Pivot)-90° ~ 90°Adjustment (Height)0 ~ 130 mmKensington LockYesDimension (W x D x H)613 x 228 x 539 mm 613 x 61 x 369 mm (without Stand)Carton Dimension (W X D X H)WW: 840 x 150 x 475 mm Outer:858 x 165 x 500 mmFrameless DesignYes	Viewing Angle	178° (H) / 178° (V)
Display Colors         1.07B (8 bits + FRC)           Power Type         External Adaptor           Power Input         100~240V, 50/60Hz           Adjustment (Tilt)         -5° ~ 20°           Adjustment (Swivel)         -30° ~ 30°           Adjustment (Pivot)         -90° ~ 90°           Adjustment (Height)         0 ~ 130 mm           Kensington Lock         Yes           Dimension (W x D x H)         613 x 228 x 539 mm (without Stand)           Carton Dimension (W X D X H)         WW: 840 x 150 x 475 mm Outer:858 x 165 x 500 mm           Frameless Design         Yes	Adobe RGB / DCI-P3 / sRGB	90% / 94% / 125%
Power Type         External Adaptor           Power Input         100~240V, 50/60Hz           Adjustment (Tilt)         -5° ~ 20°           Adjustment (Swivel)         -30° ~ 30°           Adjustment (Pivot)         -90° ~ 90°           Adjustment (Height)         0 ~ 130 mm           Kensington Lock         Yes           Dimension (W x D x H)         613 x 228 x 539 mm (without Stand)           Carton Dimension (W X D X H)         WW: 840 x 150 x 475 mm Outer:858 x 165 x 500 mm           Frameless Design         Yes	Surface Treatment	Anti-glare
Power Input         100~240V, 50/60Hz           Adjustment (Tilt)         -5° ~ 20°           Adjustment (Swivel)         -30° ~ 30°           Adjustment (Pivot)         -90° ~ 90°           Adjustment (Height)         0 ~ 130 mm           Kensington Lock         Yes           Dimension (W x D x H)         613 x 228 x 539 mm (without Stand)           613 x 61 x 369 mm (without Stand)         WW: 840 x 150 x 475 mm Outer:858 x 165 x 500 mm           Frameless Design         Yes	Display Colors	1.07B (8 bits + FRC)
Adjustment (Tilt)       -5° ~ 20°         Adjustment (Swivel)       -30° ~ 30°         Adjustment (Pivot)       -90° ~ 90°         Adjustment (Height)       0 ~ 130 mm         Kensington Lock       Yes         Dimension (W x D x H)       613 x 228 x 539 mm (without Stand)         Carton Dimension (W X D X H)       WW: 840 x 150 x 475 mm Outer:858 x 165 x 500 mm         Frameless Design       Yes	Power Type	External Adaptor
Adjustment (Swivel)       -30° ~ 30°         Adjustment (Pivot)       -90° ~ 90°         Adjustment (Height)       0 ~ 130 mm         Kensington Lock       Yes         Dimension (W x D x H)       613 x 228 x 539 mm (without Stand)         Carton Dimension (W X D X H)       WW: 840 x 150 x 475 mm Outer:858 x 165 x 500 mm         Frameless Design       Yes	Power Input	100~240V, 50/60Hz
Adjustment (Pivot)       -90° ~ 90°         Adjustment (Height)       0 ~ 130 mm         Kensington Lock       Yes         Dimension (W x D x H)       613 x 228 x 539 mm (without Stand)         Carton Dimension (W X D X H)       WW: 840 x 150 x 475 mm Outer:858 x 165 x 500 mm         Frameless Design       Yes	Adjustment (Tilt)	-5° ~ 20°
Adjustment (Height)       0 ~ 130 mm         Kensington Lock       Yes         Dimension (W x D x H)       613 x 228 x 539 mm (sithout Stand)         Carton Dimension (W X D X H)       WW: 840 x 150 x 475 mm Outer:858 x 165 x 500 mm         Frameless Design       Yes	Adjustment (Swivel)	-30° ~ 30°
Kensington Lock         Yes           Dimension (W x D x H)         613 x 228 x 539 mm (sithout Stand)           Carton Dimension (W X D X H)         WW: 840 x 150 x 475 mm (outer: 858 x 165 x 500 mm)           Frameless Design         Yes	Adjustment (Pivot)	-90° ~ 90°
Dimension (W x D x H)         613 x 228 x 539 mm 613 x 61 x 369 mm (without Stand)           Carton Dimension (W X D X H)         WW: 840 x 150 x 475 mm Outer:858 x 165 x 500 mm           Frameless Design         Yes	Adjustment (Height)	0 ~ 130 mm
Carton Dimension (W X D X H)   613 x 61 x 369 mm (without Stand)   WW: 840 x 150 x 475 mm   Outer:858 x 165 x 500 mm   Yes	Kensington Lock	Yes
Carton Dimension (W X D X H) Outer:858 x 165 x 500 mm Yes	Dimension (W x D x H)	
	Carton Dimension (W X D X H)	
PIP / PBP Function N/A	Frameless Design	Yes
	PIP / PBP Function	N/A

## **FEATURES**



Make sure the intensity and purity of colors when gaming.



### 180Hz High Refresh Rate

Experience smooth gaming with a blazing fast 180Hz refresh rate, that gives you the upperhand in fast moving games.



### **1ms Fast Response Time**

ms Fast Response Time
GTG Eliminate screen tearing and choppy frame rates with 1ms response time.



Perfectly support 120Hz at FHD/WQHD resolution with next-gen console like PS5 and Xbox series X/S.



### **Adjustable Stand**

Through adjustments of tilting, lowering and raising, and swiveling, easily change the position of the monitor for maximum ergonomics and optimum viewing experiences.



### **Wide Color Gamut**

Wide Color Game colors and details will look more realistic and refined, to | Gamut push game immersion to its limits.





MSI gaming monitor is equipped with HDR technology that can produce images with more details, wider range of colors. Windows 11 Auto HDR supported



# MONITORS **G272QPF E2**

ALL ABOUT GAMING

VESA Mounting	100 x 100 mm
Weight (NW / GW)	6.3 / 8.4kg
Note	Display Port: 2560 x 1440 (Up to 180Hz) HDMI 2.0b: 2560 x 1440 (Up to 144Hz) Adobe RGB, DCI-P3 and sRGB and Rec.2020 follow CIE1976 Standard

# **CONNECTIONS**



© 2024 Micro-Star Int'l Co.Ltd. MSI is a registered trademark of Micro-Star Int'l Co.Ltd. All rights reserved.

- 1. 5-way joystick navigator
- 2. DC-in
- 3. 1 x Display Port (1.4)
- 4. 2 x HDMI<sup>™</sup> (2.0b)
- 5. Headphone out
- 6. Kensington lock